



HNE971H

MCCB h1000 4P 50kA 1000A LSI

Technische Merkmale

Architecture

Type of order	Toggle
Type of case	Fixed built-in
Number of poles	4 P
Type of pole	4P4D N:0;50;100%

Functions

Complete device with protection unit	yes
Trip Unit	LSI
Integrated earth fault protection	no

Compatibility

Compatible with DIN rail mounting	no
-----------------------------------	----

Controls and indicators

Motor drive integrated	no
------------------------	----

Main electrical features

Frequency	50/60 Hz
Rated operational voltage Ue	220/690 V

Voltage

Rated insulation voltage	800 V
Rated impulse withstand voltage	8000 V
With under voltage release	no

Electric current

Rated ultimate short-circuit breaking capacity Icu under 400V AC IEC 60947-2	50 kA
Rated service breaking capacity Ics AC according IEC 60947-2	100 %
Breaking capacity on 1 pole with 230 V NF 60947-2	45 kA
Breaking capacity on 1 pole with 400 V NF 60947-2	9 kA
Rated ultimate short-circuit breaking capacity Icu under 230V AC IEC 60947-2	85 kA
Rated ultimate short-circuit breaking capacity Icu under 240V AC IEC 60947-2	75 kA
Rated ultimate short-circuit breaking capacity Icu under 415V AC IEC 60947-2	50 kA
Rated ultimate short-circuit breaking capacity Icu under 440V AC IEC 60947-2	45 kA
Rated ultimate short-circuit breaking capacity Icu under 690V AC IEC 60947-2	20 kA
Thermal protection nob setting xIN	0,4/0,5/0,63/0,8/0,9/0,95/1
Thermal setting current on neutral pole	0/0,5/1 In

Current correction factors

Correction factor of rating current for 2 devices placed side-by-side	1
Correction factor of rating current for 3 devices placed side-by-side	1
Correction factor of rating current for 4 and 5 devices placed side-by-side	1
Correction factor of rating current for 6 devices placed side-by-side	1

Power

Power loss per pole at I_n	62 W
Power loss per pole at $0.63 \cdot I_n$	24,6 W
Power loss per pole at $0.8 \cdot I_n$	39,7 W
Total power loss under I_N	186 W
Total power loss at $0.63 \cdot I_n$	73,8 W
Total power loss at $0.8 \cdot I_n$	119 W

Tripping

Trip mode	LSI
Thermal protection trip time	5/10/11/16/21 ms
Time of response when opening	10 ms

Electrical specifications

Magnetic trip delay time	100 to 200 ms
--------------------------	---------------

Endurance

Electric endurance in number of cycles	1000
Number of mechanical operations	4000

Installation, mounting

Tightening torque	65 Nm
DIN rail mounting with optional adaptator	no

Connection

Connection cross-sect. rigid cable	2x240 mm ²
Connection cross-sect. flexible conductor	2x240 mm ²
Connection	Front connection
Type of connection	Terminal

Settings

Magnetic protection nob setting $\times I_N$	2,5/5/8
Setting type I_n or I_{th}	$I_r I_{th}$
Range of the magnetic adjustment	5600/7000/8820/10000/10000/10000/10000 A

Equipment

Motor drive optional	yes
----------------------	-----

Use cases	
Category of use	A
Standards	
Standard text	IEC 60947-2
European directive WEEE	concerned
Safety	
Protection index IP	IP4X
Use conditions	
Altitude	2000 m
Storage temperature	-35 to 70 °C
Air humidity protection	for all climates