



MU110A

MCB 1P 6kA C-10A 1M

Architecture

| | |
|---------------------------|----------------|
| Neutral position | not applicable |
| Number of protected poles | 1 |
| Number of poles | 1 P |
| Type of pole | 1 P |
| Fixing mode | Din-Rail |
| Curve | C |

Controls and indicators

| | |
|----------------------|----|
| With fault indicator | no |
|----------------------|----|

Connectivity

| | |
|---|------------------|
| Bottom connection alignment for modular devices | Aligned terminal |
| Top connection alignment for modular devices | Aligned terminal |

Main electrical features

| | |
|---|-----------|
| Frequency | 50/60 Hz |
| Rated short circuit breaking capacity Icn AC according IEC60898-1 | 6 kA |
| Type of supply voltage | AC |
| Rated operational voltage Ue | 230/400 V |

Voltage

| | |
|---------------------------------|--------|
| Rated insulation voltage | 500 V |
| Rated impulse withstand voltage | 4000 V |

Electric current

| | |
|--|--------------|
| Rated short circuit breaking capacity Icn under 230V AC according IEC60898-1 | 6 kA |
| Rated service breaking capacity Ics AC according IEC 60898-1 | 6 kA |
| Rated ultimate short-circuit breaking capacity Icu under 230V AC IEC 60947-2 | 6 kA |
| Magnetic regulating current at 40° C | 5/10 In |
| min/maxi threshold value of the AC thermal operation | 1,13/1,45 In |

Electric current / temperature

| | |
|----------------------|---------|
| Rating current -15°C | 12,8 A |
| Rating current -20°C | 13,1 A |
| Rating current 0°C | 11,91 A |
| Rating current 10°C | 11,31 A |
| Rating current -10°C | 12,54 A |
| Rating current 15°C | 11,01 A |
| Rating current 20°C | 10,72 A |
| Rating current 25°C | 10,42 A |
| Rating current -25°C | 13,4 A |
| Rating current 30°C | 10 A |
| Rating current 35°C | 9,82 A |
| Rating current 40°C | 9,52 A |
| Rating current 45°C | 9,22 A |
| Rating current 5°C | 11,61 A |
| Rating current -5°C | 12,21 A |
| Rating current 50°C | 9 A |
| Rating current 55°C | 8,63 A |
| Rating current 60°C | 8,33 A |
| Rating current 65°C | 8,03 A |
| Rating current 70°C | 7,73 A |

Current correction factors

| | |
|---|-----|
| Correction factor of magnetic tripping with 100 Hz | 1,1 |
| Correction factor of magnetic tripping with 200 Hz | 1,2 |
| Correction factor of magnetic tripping with 400 Hz | 1,5 |
| Correction factor of magnetic tripping with 60 Hz | 1 |
| Correction factor of rating current for 2 devices placed 1 side-by-side | |
| Correction factor of rating current for 3 devices placed 0,95 side-by-side | |
| Correction factor of rating current for 4 and 5 devices placed side-by-side | 0,9 |
| Correction factor of rating current for 6 devices placed 0,85 side-by-side | |

Power

| | |
|---------------------------------------|--------|
| Power loss per pole at I _n | 1,63 W |
| Total power loss under I _N | 1,63 W |

Endurance

| | |
|--|-------|
| Electric endurance in number of cycles | 4000 |
| Number of mechanical operations | 20000 |

Dimensions

| | |
|-----------------------------|---------|
| Depth of installed product | 70 mm |
| Height of installed product | 83 mm |
| Width of installed product | 17,5 mm |

Installation, mounting

| | |
|---|------------|
| Type of top connection for modular devices | with screw |
| Tightening torque | 2,8Nm |
| Type of bottom rail clip for modular devices | metallic |
| Type of top rail clip for modular devices | NA |
| Type of Bottom Connection for modular devices | Blconnect |
| Bottom removability for modular devices | no |

Technical Properties

| | |
|--------------------------------------|----|
| Top removability for modular devices | no |
|--------------------------------------|----|

Connection

| | |
|--|-----------------------|
| Connection cross-sect. rigid cable | 1 / 35mm ² |
| Connection cross-sect. flexible conductor | 1 / 25mm ² |
| Type of connection | with screw |
| Connection cross section of access and exit with screws, for flexible conductor | 1/25 mm ² |
| Connection cross-section of input and output with screws, for massive conductors | 1/35 mm ² |

Equipment

| | |
|---------------|----|
| Quick connect | no |
|---------------|----|

Standards

| | |
|-------------------------|-------------|
| Standard text | IEC 60898-1 |
| European directive WEEE | concerned |

Safety

| | |
|---------------------|------|
| Protection index IP | IP20 |
|---------------------|------|

Use conditions

| | |
|--|------------------|
| Degree of pollution according to IEC 60664 / IEC 60947-2 | 2 |
| Operating temperature | -25 70 °C |
| Class of energy limitation I ² t | 3 |
| Altitude | 2000 m |
| Storage temperature | -25 to 80 °C |
| Air humidity protection | for all climates |
| Storage/transport temperature | -25 80 °C |