MCB 2P 6kA C-40A 2M

Technische Merkmale

Architecture

Neutral position	not applicable
Number of protected poles	2
Number of poles	2 P
Type of pole	2 P
Fixing mode	Din-Rail
Curve	C

Controls and indicators

With fault indicator	no

Connectivity

Bottom connection alignement for modular devices	Aligned terminal
Top connection alignement for modular devices	Aligned terminal

Main electrical features

Frequency	50/60 Hz
Rated short circuit breaking capacity Icn AC according IEC60898-1	6 kA
Type of supply voltage	AC
Rated operational voltage Ue	400 V

Voltage

Rated insulation voltage	500 V
Rated impulse withstand voltage	4000 V

Electric current

Rated short circuit breaking capacity Icn under 400V AC according IEC60898-1	6 kA
Rated service breaking capacity Ics AC according IEC 60898-1	6 kA
Breaking capacity on 1 pole with 400 V NF 60947-2	3 kA
Rated ultimate short-circuit breaking capacity Icu under 415V AC IEC 60947-2	10 kA
Magnetic regulating currrent at 40° C	5/10 In
min/maxi threshold value of the DC magnetic operation	7/15 In
min/maxi threshold value of the AC thermal operation	1,13/1,45 In
min/maxi threshold value of the DC thermal operation	1,13/1,45 In

Electric current / temperature

Rating current -15°C	45,6 A
Rating current -20°C	46,2 A
Rating current 0°C	43,8 A
Rating current 10°C	42,6 A
Rating current -10°C	45 A
Rating current 15°C	42 A
Rating current 20°C	41,3 A
Rating current 25°C	40,7 A
Rating current -25°C	46,8 A
Rating current 30°C	40 A
Rating current 35°C	39,3 A
Rating current 40°C	38,6 A
Rating current 45°C	37,9 A
Rating current 5°C	43,2 A
Rating current -5°C	44,4 A
Rating current 50°C	37,2 A
Rating current 55°C	36,5 A
Rating current 60°C	35,7 A
Rating current 65°C	35,1 A
Rating current 70°C	34,3 A

Current correction factors

Correction factor of magnetic tripping with 100 Hz	1,1
Correction factor of magnetic tripping with 200 Hz	1,2
Correction factor of magnetic tripping with 400 Hz	1,5
Correction factor of magnetic tripping with 60 Hz	1
Correction factor of rating current for 2 devices placed side-by-side	1
Correction factor of rating current for 3 devices placed side-by-side	0,95
Correction factor of rating current for 4 and 5 devices placed side-by-side	0,9
Correction factor of rating current for 6 devices placed side-by-side	0,85

Power

Power loss per pole at In	4,92 W
Total power loss under IN	9,6 W

Endurance

Electric endurance in number of cycles	4000
Number of mechanical operations	20000

Dimensions

Depth of installed product	70 mm
Height of installed product	83 mm
Width of installed product	35 mm

Installation, mounting

Type of top connection for modular devices	with screw
Tightening torque	2,8Nm
Type of bottom rail clip for modular devices	metallic
Type of top rail clip for modular devices	NA
Type of Bottom Connection for modular devices	BIconnect
Bottom removability for modular devices	no
Top removability for modular devices	no

Connection

Connection cross-sect. rigid cable	1 / 35mm²
Connection cross-sect. flexible conductor	1 / 25mm²
Type of connection	with screw
Connection cross section of access and exit with screws, for flexible conductor	1/25 mm²
Connection cross-section of input and output with screws, for massive conductors	1/35 mm²

Equipment

Quick connect	no

Standards

Standard text	IEC 60898-1
European directive WEEE	concerned

Safety

Protection index IP	IP20

Use conditions

Degree of pollution according to IEC 60664 / IEC 60947-2	2
Operating temperature	-25 … 70 °C
Class of energy limitation I²t	3
Altitude	2000 m
Storage temperature	-25 to 80 °C
Air humidity protection	for all climates
Storage/transport temperature	-25 … 80 °C