



MCB 2P 3kA C-20A 2M

MW220

Architecture

Number of poles	2 P
Type of pole	2 P
Curve	C

Main electrical features

Frequency	50/60 Hz
Rated short circuit breaking capacity I _{cn} AC according IEC60898-1	3 kA
Rated operational voltage U _e	230/400 V

Voltage

Rated insulation voltage	500 V
Rated impulse withstand voltage	4000 V

Electric current

Rated short circuit breaking capacity I _{cn} under 400V AC according IEC60898-1	3 kA
Rated service breaking capacity I _{cs} AC according IEC 60898-1	3 kA
Breaking capacity on 1 pole with 400 V NF 60947-2	3 kA
Rated ultimate short-circuit breaking capacity I _{cu} under 415V AC IEC 60947-2	4,5 kA
Magnetic regulating current at 40° C	5/10 I _n
min/maxi threshold value of the DC magnetic operation	5/15 I _n
min/maxi threshold value of the AC thermal operation	1,13/1,45 I _n
min/maxi threshold value of the DC thermal operation	1,13/1,45 I _n

Electric current / temperature

Rating current -15°C	23,2 A
Rating current -20°C	23,5 A
Rating current 0°C	22,2 A
Rating current 10°C	21,5 A
Rating current -10°C	22,8 A
Rating current 15°C	21,1 A
Rating current 20°C	20,7 A
Rating current 25°C	20,4 A

Technical Properties

Rating current -25°C	23,8 A
Rating current 30°C	20 A
Rating current 35°C	19,6 A
Rating current 40°C	19,2 A
Rating current 45°C	18,8 A
Rating current 5°C	21,8 A
Rating current -5°C	22,5 A
Rating current 50°C	18,4 A
Rating current 55°C	18 A
Rating current 60°C	17,6 A
Rating current 65°C	17,2 A
Rating current 70°C	16,8 A

Current correction factors

Correction factor of magnetic tripping with 100 Hz	1,1
Correction factor of magnetic tripping with 200 Hz	1,2
Correction factor of magnetic tripping with 400 Hz	1,5
Correction factor of magnetic tripping with 60 Hz	1
Correction factor of rating current for 2 devices placed 1 side-by-side	
Correction factor of rating current for 3 devices placed 0,95 side-by-side	
Correction factor of rating current for 4 and 5 devices placed side-by-side	0,9
Correction factor of rating current for 6 devices placed side-by-side	0,85

Power

Power loss per pole at In	2,78 W
Total power loss under IN	5,5 W

Endurance

Electric endurance in number of cycles	10000
Number of mechanical operations	20000

Dimensions

Depth of installed product	70 mm
Height of installed product	83 mm
Width of installed product	35 mm

Installation, mounting

Tightening torque	2,8Nm
-------------------	-------

Connection

type of connection	with screw
Top and bottom screw terminals connection capacity with flexible cable	1/16 mm ²
Top and bottom screw terminals connection capacity with rigid cable	1/25 mm ²

Standards

Standard text	EN 60898-1
European directive RoHs	voluntary compliance
European directive WEEE	not concerned

Use conditions

Degree of pollution according to IEC 60664 / IEC 60947-2	2
Class of energy limitation I ² t	3
Altitude	2000 m
Storage temperature	-25 to 80 °C
Air humidity protection	for all climates