


NDN263A



NDN263A

MCB 2P 10kA D-63A 2M

Technische Merkmale

Architecture

| | |
|---------------------------|-----------------|
| Neutral position | without neutral |
| Number of protected poles | 2 |
| Number of poles | 2 P |
| Type of pole | 2 P |
| Curve | D |

Connectivity

| | |
|---|------------------|
| Bottom connection alignment for modular devices | Aligned terminal |
| Top connection alignment for modular devices | Aligned terminal |

Main electrical features

| | |
|---------------------------------|-------|
| Type of supply voltage | AC |
| Rated operational voltage U_e | 415 V |

Voltage

| | |
|---|--------|
| Minimum threshold voltage ($U_e \text{ min}$) | 12 V |
| Rated insulation voltage | 500 V |
| Max operating voltage | 440 V |
| Rated impulse withstand voltage | 6000 V |

Electric current

| | |
|---|--------------|
| Rated ultimate short-circuit breaking capacity Icu under 400V AC IEC 60947-2 | 15 kA |
| Rated short circuit breaking capacity Icn under 230V AC according IEC60898-1 | 10 kA |
| Rated short circuit breaking capacity Icn under 400V AC according IEC60898-1 | 10 kA |
| Rated short circuit breaking capacity Icn under 240V AC according IEC 60898-1 | 10 kA |
| Rated short circuit breaking capacity Icn under 380V AC according IEC 60898-1 | 10 kA |
| Rated short circuit breaking capacity Icn under 415V AC according IEC 60898-1 | 10 kA |
| Rated service breaking capacity Ics AC according IEC 60898-1 | 7,5 kA |
| Rated service breaking capacity Ics under 220V AC according IEC 60947-2 | 15 kA |
| Rated service breaking capacity Ics under 230V AC according IEC 60947-2 | 15 kA |
| Rated service breaking capacity Ics under 240V AC according IEC 60947-2 | 15 kA |
| Rated service breaking capacity Ics under 380V AC according IEC 60947-2 | 7,5 kA |
| Rated service breaking capacity Ics under 400V AC according IEC 60947-2 | 7,5 kA |
| Rated service breaking capacity Ics under 415V AC according IEC 60947-2 | 7,5 kA |
| Rated service breaking capacity Ics under 220V AC according IEC 60898-1 | 7,5 kA |
| Rated service breaking capacity Ics under 230V AC according IEC 60898-1 | 7,5 kA |
| Rated service breaking capacity Ics under 240V AC according IEC 60898-1 | 7,5 kA |
| Rated service breaking capacity Ics under 380V AC according IEC 60898-1 | 7,5 kA |
| Rated service breaking capacity Ics under 400V AC according IEC 60898-1 | 7,5 kA |
| Rated service breaking capacity Ics under 415V AC according IEC 60898-1 | 7,5 kA |
| Rated ultimate short-circuit breaking capacity Icu under 220V AC IEC 60947-2 | 30 kA |
| Rated ultimate short-circuit breaking capacity Icu under 230V AC IEC 60947-2 | 30 kA |
| Rated ultimate short-circuit breaking capacity Icu under 240V AC IEC 60947-2 | 30 kA |
| Rated ultimate short-circuit breaking capacity Icu under 380V AC IEC 60947-2 | 15 kA |
| Rated ultimate short-circuit breaking capacity Icu under 415V AC IEC 60947-2 | 15 kA |
| Magnetic regulating current at 40° C | 10/14,4 In |
| min/maxi threshold value of the DC magnetic operation | 15/30 In |
| min/maxi threshold value of the AC thermal operation | 1,13/1,45 In |
| min/maxi threshold value of the DC thermal operation | 1,13/1,45 In |

Electric current / temperature

| | |
|---|---------|
| Rating current -15°C | 78,07 A |
| Rating current -20°C | 79,57 A |
| Rating current 0°C | 73,54 A |
| Rating current 10°C | 70,52 A |
| Rating current -10°C | 76,54 A |
| Rating current 25°C | 65,95 A |
| Rating current -25°C | 81,04 A |
| Rating current 30°C | 63 A |
| Rating current 35°C | 62,03 A |
| Rating current 40°C | 60,5 A |
| Rating current 45°C | 58,68 A |
| Rating current 5°C | 72,03 A |
| Rating current -5°C | 75,05 A |
| Rating current 50°C | 58,27 A |
| Rating current 55°C | 52,8 A |
| Rating current 60°C | 50,51 A |
| Rating current 65°C | 48,12 A |
| Rating current 70°C | 45,6 A |
| Rating current 0°C according to IEC 60947-2 | 84,08 A |
| Rating current 10°C according to IEC 60947-2 | 80,31 A |
| Rating current -10°C according to IEC 60947-2 | 87,69 A |
| Rating current 150°C according to IEC 60947-2 | 78,36 A |
| Rating current -15°C according to IEC 60947-2 | 89,44 A |
| Rating current 20°C according to IEC 60947-2 | 76,35 A |
| Rating current -20°C according to IEC 60947-2 | 91,16 A |
| Rating current 25°C according to IEC 60947-2 | 74,29 A |
| Rating current -25°C according to IEC 60947-2 | 92,84 A |
| Rating current 30°C according to IEC 60947-2 | 73,2 A |
| Rating current 35°C according to IEC 60947-2 | 70,4 A |
| Rating current 40°C according to IEC 60947-2 | 67,9 A |
| Rating current 45°C according to IEC 60947-2 | 65,3 A |
| Rating current 5°C according to IEC 60947-2 | 82,22 A |
| Rating current -5°C according to IEC 60947-2 | 85,91 A |
| Rating current 50°C according to IEC 60947-2 | 63 A |
| Rating current 55°C according to IEC 60947-2 | 60,2 A |
| Rating current 60°C according to IEC 60947-2 | 57,7 A |
| Rating current 65°C according to IEC 60947-2 | 55,1 A |
| Rating current 70°C according to IEC 60947-2 | 52,6 A |

Current correction factors

| | |
|---|------|
| Correction factor of magnetic tripping with 100 Hz | 1,1 |
| Correction factor of magnetic tripping with 200 Hz | 1,2 |
| Correction factor of magnetic tripping with 400 Hz | 1,5 |
| Correction factor of magnetic tripping with 60 Hz | 1,1 |
| Correction factor of rating current for 2 devices placed side-by-side | 1 |
| Correction factor of rating current for 3 devices placed side-by-side | 0,95 |
| Correction factor of rating current for 4 and 5 devices placed side-by-side | 0,9 |
| Correction factor of rating current for 6 devices placed side-by-side | 0,85 |

Power

| | |
|---|--------|
| Power loss per pole at In | 6,99 W |
| Maximum power loss per pole according to the product standard | 13 W |
| Total power loss under IN | 13,1 W |

Endurance

| | |
|--|-------|
| Electric endurance in number of cycles | 4000 |
| Number of mechanical operations | 20000 |

Dimensions

| | |
|-----------------------------|-------|
| Depth of installed product | 70 mm |
| Height of installed product | 83 mm |
| Width of installed product | 35 mm |

Installation, mounting

| | |
|---|------------|
| Type of top connection for modular devices | with screw |
| Tightening torque | 2,8Nm |
| Type of bottom rail clip for modular devices | plastic |
| Type of top rail clip for modular devices | NA |
| Type of Bottom Connection for modular devices | Blconnect |
| Bottom removability for modular devices | yes |
| Top removability for modular devices | yes |
| Suitable for flush-mounting | yes |

Connection

| | |
|--|----------------------|
| Upstream cage clamp delivery status | opened |
| Downstream cage clamp delivery status | opened |
| Connection cross-section at output with screw, for flexible conductor | 1/25 mm ² |
| Connection cross-section of the access with screws, with flexible conductor | 1/25 mm ² |
| Connection cross-section at output with screw, for massive conductor | 1/35 mm ² |
| Connection cross-section for rigid conductor, upstream terminals with screws | 1/35 mm ² |

Equipment

| | |
|---------------------|-----|
| Can be accessorized | yes |
|---------------------|-----|

Standards

| | |
|-------------------------|----------------------------|
| Standard text | EN 60898-1, AS/NZS 60898-1 |
| European directive WEEE | concerned |

Safety

| | |
|---------------------|------|
| Protection index IP | IP20 |
|---------------------|------|

Use conditions

| | |
|--|--------------|
| Degree of pollution according to IEC 60664 / IEC 60947-2 | 2 |
| Altitude | 2000 m |
| Storage temperature | -25 to 80 °C |

temperatur

| | |
|----------------------------|-------|
| Temperature of calibration | 30 °C |
|----------------------------|-------|
