



NRN163

## MCB 1P 15kA C-63A 1M

### Technische Merkmale

#### Architecture

Neutral position	without neutral
Number of protected poles	1
Number of poles	1 P
Type of pole	1 P
Fixing mode	Din-Rail
Curve	C

#### Controls and indicators

With fault indicator	no
----------------------	----

#### Connectivity

Bottom connection alignment for modular devices	Aligned terminal
Top connection alignment for modular devices	Aligned terminal

#### Main electrical features

Frequency	50/60 Hz
Type of supply voltage	AC
Rated operational voltage Ue	240/415 V

#### Voltage

Minimum threshold voltage (Ue min)	12 V
Rated insulation voltage	500 V
Rated impulse withstand voltage	6000 V

#### Electric current

Breaking capacity on 1 pole with 400 V NF 60947-2	3 kA
Magnetic regulating current at 40° C	5/10 In
min/maxi threshold value of the DC magnetic operation	5/15 In
min/maxi threshold value of the AC thermal operation	1,13/1,45 In
min/maxi threshold value of the DC thermal operation	1,13/1,45 In

### Current correction factors

Correction factor of magnetic tripping with 100 Hz	1,1
Correction factor of magnetic tripping with 200 Hz	1,2
Correction factor of magnetic tripping with 400 Hz	1,5
Correction factor of magnetic tripping with 60 Hz	1
Correction factor of rating current for 2 devices placed side-by-side	1
Correction factor of rating current for 3 devices placed side-by-side	0,95
Correction factor of rating current for 4 and 5 devices placed side-by-side	0,9
Correction factor of rating current for 6 devices placed side-by-side	0,85

### Power

Power loss per pole at I <sub>n</sub>	5,73 W
Total power loss under I <sub>N</sub>	5,73 W

### Endurance

Electric endurance in number of cycles	4000
Number of mechanical operations	20000

### Dimensions

Depth of installed product	70 mm
Height of installed product	83 mm
Width of installed product	17,5 mm

### Installation, mounting

Type of top connection for modular devices	with screw
Tightening torque	2,8Nm
Type of bottom rail clip for modular devices	plastic
Type of top rail clip for modular devices	NA
Type of Bottom Connection for modular devices	Blconnect
Bottom removability for modular devices	yes
Top removability for modular devices	yes

### Connection

Type of connection	with screw
Connection cross section of access and exit with screws, for flexible conductor	1/25 mm <sup>2</sup>
Connection cross-section of input and output with screws, for massive conductors	1/35 mm <sup>2</sup>

### Standards

Standard text	IEC 60947-2
European directive WEEE	concerned

### Safety

Protection index IP	IP20
---------------------	------

**Use conditions**

Degree of pollution according to IEC 60664 / IEC 60947-2	2
Operating temperature	-25 ... 70 °C
Class of energy limitation I²t	3
Altitude	2000 m
Storage temperature	-25 to 80 °C
Air humidity protection	for all climates
Storage/transport temperature	-25 ... 80 °C