



BE464

Add-on block 4P 63A 100mA AC

Technische Merkmale

Architecture

Neutral position	left
Number of poles	4 P

Main electrical features

Frequency	50 Hz
Rated operational voltage Ue	230/400 V

Voltage

Rated insulation voltage	500 V
Rated impulse withstand voltage	4000 V

Electric current

Rated residual operating current	100 mA
----------------------------------	--------

Electric current / temperature

Rating current 40°C	63 A
---------------------	------

Power

Power loss per pole at I _n	10,7 W
Total power loss under I _N	35,5 W

Tripping

Protected against nuisance tripping	no
-------------------------------------	----

Endurance

Electric endurance in number of cycles	2000
Number of mechanical operations	1000

Dimensions

Depth of installed product	9,2 cm
Height of installed product	7 cm
Width of installed product	3,5 cm

Installation, mounting

Tightening torque	2,8Nm
Type of bottom rail clip for modular devices	NA
Type of top rail clip for modular devices	Plastic
Bottom removability for modular devices	no
Top removability for modular devices	yes

Connection

Connection cross-sect. rigid cable	25mm ²
Connection cross-sect. flexible conductor	16mm ²

Settings

Rated fault current adjustable	no
Delay adjustable	no

Standards

European directive WEEE	concerned
-------------------------	-----------

Safety

Protection index IP	IP20
Residual current type	AC

Use conditions

Operating temperature	-25 ... 70 °C
Altitude	2000 m
Storage temperature	-25 to 70 °C
Air humidity protection	Execution I
