



AEC125

RCBO 1M 1P 10kA C-25A 100mA AC

Architecture

Neutral position	right
Number of protected poles	1
Number of poles	1 P
Type of pole	1 P
Fixing mode	Din-Rail
Curve	C

Compatibility

Compatible with DIN rail mounting	yes
-----------------------------------	-----

Controls and indicators

With fault indicator	no
----------------------	----

Main electrical features

Frequency	50/60 Hz
Rated short circuit breaking capacity Icn AC according 10 kA IEC60898-1	
Rated operational voltage Ue	230/240 V

Voltage

Rated insulation voltage	250 V
Max operating voltage	253 V
Rated impulse withstand voltage	4000 V

Electric current

Rated residual operating current	100 mA
Withstand not tripping on 8-20 ?s wave	3 kA
Rated short circuit breaking capacity Icn under 230V AC according IEC60898-1	10 kA
Breaking and opening capacity	6 kA
Magnetic regulating current at 40° C	5/10 In
min/maxi threshold value of the AC thermal operation	1,13/1,45 In

#### Electric current / temperature

Rating current -15°C	30,3 A
Rating current -20°C	30,83 A
Rating current 0°C	28,64 A
Rating current 10°C	27,48 A
Rating current -10°C	29,76 A
Rating current 15°C	26,88 A
Rating current 20°C	26,27 A
Rating current 25°C	25,64 A
Rating current -25°C	31,35 A
Rating current 30°C	25 A
Rating current 35°C	24,34 A
Rating current 40°C	23,66 A
Rating current 45°C	22,96 A
Rating current 5°C	28,07 A
Rating current -5°C	29,2 A
Rating current 50°C	22,24 A
Rating current 55°C	21,5 A
Rating current 60°C	20,73 A

#### Current correction factors

Correction factor of rating current for 2 devices placed 1 side-by-side	
Correction factor of rating current for 3 devices placed 0,95 side-by-side	
Correction factor of rating current for 4 and 5 devices placed side-by-side	0,9
Correction factor of rating current for 6 devices placed side-by-side	0,85

#### Power

Power loss per pole at In	3,6 W
Total power loss under IN	6,9 W

#### Tripping

Protected against nuisance tripping	no
-------------------------------------	----

#### Endurance

Electric endurance in number of cycles	2000
Number of mechanical operations	2000

#### Dimensions

Depth of installed product	70 mm
Height of installed product	110 mm
Width of installed product	17,8 mm

#### Installation, mounting

Tightening torque	2,1Nm
Type of bottom rail clip for modular devices	metallic isolated
Type of top rail clip for modular devices	NA
Bottom removability for modular devices	no
Top removability for modular devices	no

#### Connection

Connection cross-section at output with screw, for flexible conductor	1/16 mm <sup>2</sup>
---	----------------------

Connection cross-section of the access with screws, with flexible conductor	1/16 mm <sup>2</sup>
---	----------------------

Connection cross-section at output with screw, for massive conductor	1/25 mm <sup>2</sup>
--	----------------------

Connection cross-section for rigid conductor, upstream terminals with screws	1/25 mm <sup>2</sup>
--	----------------------

#### Standards

Standard text	IEC 61009-1
---------------	-------------

European directive WEEE	not concerned
-------------------------	---------------

#### Safety

Protection index IP	IP20
---------------------	------

Residual current type	AC
-----------------------	----

#### Use conditions

Degree of pollution according to IEC 60664 / IEC 60947-2	2
--	---

Class of energy limitation I <sup>2</sup> t	3
---	---

Altitude	2000 m
----------	--------

Air humidity protection	Execution II
-------------------------	--------------