



RCBO 1P+N 6kA C-32A 30mA AC

AD982B

#### Architecture

Neutral position	right
Number of protected poles	1
Number of poles	2 P
Type of pole	1P+N
Curve	C

#### Main electrical features

Frequency	50 Hz
Rated short circuit breaking capacity $I_{cn}$ AC according IEC60898-1	6 kA
Rated operational voltage $U_e$	240 V

#### Voltage

Rated insulation voltage	500 V
Max operating voltage	240 V
Rated impulse withstand voltage	4000 V

#### Electric current

Rated residual operating current	30 mA
Withstand not tripping on 8-20 $\mu$ s wave	250 A
Rated short circuit breaking capacity $I_{cn}$ under 230V AC according IEC60898-1	6 kA
Rated ultimate short-circuit breaking capacity $I_{cu}$ under 230V AC IEC 60947-2	6 kA
Rated ultimate short-circuit breaking capacity $I_{cu}$ under 240V AC IEC 60947-2	6 kA
Breaking and opening capacity	6 kA
Magnetic regulating current at 40° C	5/10 In
min/maxi threshold value of the AC thermal operation	1,13/1,45 In

#### Electric current / temperature

Rating current -15°C	37,2 A
Rating current -20°C	37,8 A
Rating current 0°C	35,6 A
Rating current 10°C	34,4 A
Rating current -10°C	36,7 A
Rating current 15°C	33,8 A

#### Technical Properties

Rating current 20°C	33,2 A
Rating current 25°C	32,6 A
Rating current -25°C	38,3 A
Rating current 30°C	32 A
Rating current 35°C	31,5 A
Rating current 40°C	31 A
Rating current 45°C	30,5 A
Rating current 5°C	35 A
Rating current -5°C	36,1 A
Rating current 50°C	30 A
Rating current 55°C	29,5 A
Rating current 60°C	29 A

#### Current correction factors

Correction factor of rating current for 2 devices placed 1 side-by-side	
Correction factor of rating current for 3 devices placed 0,95 side-by-side	
Correction factor of rating current for 4 and 5 devices 0,9 placed side-by-side	
Correction factor of rating current for 6 devices placed 0,85 side-by-side	

#### Selectivity

Minimal rating current of upstream aM fuse for selectivity on short-circuit	40 A
Minimal rating current of upstream gL fuse for selectivity on short-circuit	50 A
Maximal rating current of downstream aM fuse for selectivity on short-circuit	8 A
Maximal rating current of downstream gL fuse for selectivity on short-circuit	16 A

#### Power

Power loss per pole at In	5,4 W
Total power loss under IN	8,3 W

#### Tripping

Protected against nuisance tripping	no
-------------------------------------	----

#### Endurance

Electric endurance in number of cycles	2000
Number of mechanical operations	1000

#### Dimensions

Depth of installed product	68 mm
Height of installed product	83 mm
Width of installed product	35 mm

#### Connection

Connection cross-section at output with screw, for flexible conductor	1/16 mm <sup>2</sup>
Connection cross-section of the access with screws, with flexible conductor	1/16 mm <sup>2</sup>

#### Technical Properties

Connection cross-section at output with screw, for massive conductor	1/25 mm <sup>2</sup>
Connection cross-section for rigid conductor, upstream terminals with screws	1/25 mm <sup>2</sup>
Connection cross-sect. rigid cable	1 / 25mm <sup>2</sup>
Connection cross-sect. flexible conductor	1 / 16mm <sup>2</sup>
Type of connection	with screw

#### Standards

Standard text	IEC 61009-1
European directive WEEE	concerned

#### Safety

Protection index IP	IP20
Residual current type	AC

#### Use conditions

Degree of pollution according to IEC 60664 / IEC 60947-2	2
Class of energy limitation I <sup>2</sup> t	3
Altitude	2000 m
Storage temperature	-25 to 70 °C
Air humidity protection	for all climates

#### temperatur

Temperature of calibration	30 °C
----------------------------	-------