

**RCBO 1P+N 6kA C-10A 300mA AC**

Technische Merkmale

**Architecture**

Neutral position	right
Number of protected poles	1
Number of poles	2 P
Type of pole	1P+N
Curve	C

**Main electrical features**

Frequency	50 Hz
Rated short circuit breaking capacity $I_{cn}$ AC according IEC60898-1	6 kA
Rated operational voltage $U_e$	240 V

**Voltage**

Rated insulation voltage	500 V
Max operating voltage	240 V
Rated impulse withstand voltage	4000 V

**Electric current**

Rated residual operating current	300 mA
Withstand not tripping on 8-20 $\mu$ s wave	250 A
Rated short circuit breaking capacity $I_{cn}$ under 230V AC according IEC60898-1	6 kA
Rated ultimate short-circuit breaking capacity $I_{cu}$ under 230V AC IEC 60947-2	6 kA
Rated ultimate short-circuit breaking capacity $I_{cu}$ under 240V AC IEC 60947-2	6 kA
Breaking and opening capacity	6 kA
Magnetic regulating current at 40° C	5/10 $I_n$
min/maxi threshold value of the AC thermal operation	1,13/1,45 $I_n$

**Electric current / temperature**

Rating current -15°C	11,7 A
Rating current -20°C	11,8 A
Rating current 0°C	11,1 A
Rating current 10°C	10,8 A
Rating current -10°C	11,5 A
Rating current 15°C	10,6 A
Rating current 20°C	10,4 A
Rating current 25°C	10,2 A
Rating current -25°C	12 A
Rating current 30°C	10 A
Rating current 35°C	9,9 A
Rating current 40°C	9,7 A
Rating current 45°C	9,6 A
Rating current 5°C	11 A
Rating current -5°C	11,3 A
Rating current 50°C	9,4 A
Rating current 55°C	9,3 A
Rating current 60°C	9,1 A

**Current correction factors**

Correction factor of rating current for 2 devices placed side-by-side	1
Correction factor of rating current for 3 devices placed side-by-side	0,95
Correction factor of rating current for 4 and 5 devices placed side-by-side	0,9
Correction factor of rating current for 6 devices placed side-by-side	0,85

**Selectivity**

Minimal rating current of upstream aM fuse for selectivity on short-circuit	12 A
Minimal rating current of upstream gL fuse for selectivity on short-circuit	16 A
Maximal rating current of downstream aM fuse for selectivity on short-circuit	2 A
Maximal rating current of downstream gL fuse for selectivity on short-circuit	6 A

**Power**

Power loss per pole at I <sub>n</sub>	2,3 W
Total power loss under I <sub>N</sub>	2,6 W

**Tripping**

Protected against nuisance tripping	no
-------------------------------------	----

**Endurance**

Electric endurance in number of cycles	2000
Number of mechanical operations	2000

### Dimensions

Depth of installed product	68 mm
Height of installed product	83 mm
Width of installed product	35 mm

### Connection

Connection cross-section at output with screw, for flexible conductor	1/16 mm <sup>2</sup>
Connection cross-section of the access with screws, with flexible conductor	1/16 mm <sup>2</sup>
Connection cross-section at output with screw, for massive conductor	1/25 mm <sup>2</sup>
Connection cross-section for rigid conductor, upstream terminals with screws	1/25 mm <sup>2</sup>
Connection cross-sect. rigid cable	1 / 25mm <sup>2</sup>
Connection cross-sect. flexible conductor	1 / 16mm <sup>2</sup>
Type of connection	with screw

### Standards

Standard text	IEC 61009-1
European directive WEEE	not concerned

### Safety

Protection index IP	IP20
Residual current type	AC

### Use conditions

Degree of pollution according to IEC 60664 / IEC 60947-2	2
Class of energy limitation I <sup>2</sup> t	3
Altitude	2000 m
Storage temperature	-25 to 70 °C
Air humidity protection	for all climates

### temperatur

Temperature of calibration	30 °C
----------------------------	-------