



LS704

Fuse carrier 3P+N 125A L58 acc. 8M

Technische Merkmale

Architecture

Number of poles	4 P
Type of pole	3P+N

Controls and indicators

Indicator lamp	no
----------------	----

Connectivity

Top connection alignment for modular devices	Aligned terminal
--	------------------

Main electrical features

Frequency	50 Hz
Rated operational voltage Ue	690 V

Electric current

Rating current of fuse cartridge	20/25/32/40/50/63/80/100/125 A
----------------------------------	--------------------------------

Current correction factors

Correction factor of the acceptable current of juxtaposition > 10 phases	0,7
Correction factor of acceptable current rating for 1-3 phase placed side-by-side	1
Correction coef of the acceptable current of juxtaposition from 4 to 6 phases	0,9
Correction factor of acceptable current rating for 7-9 phases placed side-by-sid	0,85
Correction coefficient of the acceptable current with 20°C	1
Correction factor of acceptable current rating with 30°C	0,95
Correction coefficient of the acceptable current up to 40°C	0,9
Correction coefficient of the acceptable current up to 50°C	0,8

Fuse

CharactFuse	gG
Fuse Size	22 x 58

Power

Power loss per pole at In	2,72 W
Total power loss under IN	41,88 W

Endurance

Number of mechanical operations	5000
---------------------------------	------

Dimensions

Depth of installed product	96 mm
Height of installed product	125 mm
Width of installed product	140 mm

Installation, mounting

Tightening torque	3,6Nm
-------------------	-------

Connection

Connection cross-sect. rigid cable	50mm ² max.
Connection cross-sect. flexible conductor	35 mm ² max.

Standards

European directive WEEE	concerned
-------------------------	-----------

Safety

Protection index IP	IP20
---------------------	------

Use conditions

Degree of pollution according to IEC 60664 / IEC 60947-2	3
Storage temperature	-25 to 80 °C

temperatur

Temperature of calibration	30 °C
----------------------------	-------