



MZ201

Auxiliary contact 1C+1O 6A 240V AC

Technische Merkmale

Main electrical features

Type of supply voltage	AC
Rated operational voltage U _e	230/415 V

Voltage

Rated insulation voltage	4000 V
Max operating voltage	240 V
Rated operational voltage in DC	12/250 V

Electric current

Acceptable current rating with AC1	6 A
I _{min} =f(U=12V DC) for power circuit	0,3 A
I _{min} = f (U = 230 V DC)	0,6 A
I _{min} =f(U=400V AC) for power circuit	3 A

Power

Total power loss under I _N	0,1 W
---------------------------------------	-------

Endurance

Electric endurance in number of cycles	6000
Number of mechanical operations	12000

Dimensions

Depth of installed product	40 mm
Height of installed product	80 mm
Width of installed product	9,5 mm

Installation, mounting

Tightening torque	1,2Nm
Factory fitted	no

Connection

Connection cross-sect. rigid cable	10mm ²
Connection cross-sect. flexible conductor	6mm ²
Type of connection	with screw
Type of contacts	1NC+1NO

Equipment

Quantity of NC contacts	1
Quantity of NO contacts	1

Standards

European directive WEEE	concerned
-------------------------	-----------

Use conditions

Storage temperature	-40 to 80 °C
Air humidity protection	95% / 80°C
