



CZ001

Contact for RCCB 2(1C+10) 6A 240V AC

Technische Merkmale

Main electrical features

Frequency	50 Hz
Rated operational voltage Ue	230/440 V

Voltage

Rated insulation voltage	500 V
Rated operational voltage in DC	12/250 V

Electric current

Acceptable current rating with AC1	6 A
I _{min} = f (U = 230 V AC)	6 A
I _{min} = f (U = 230 V DC)	0,6 A
I _{min} =f(U=400V AC) for power circuit	3 A

Power

Total power loss under I _N	0,1 W
---------------------------------------	-------

Endurance

Electric endurance in number of cycles	6000
Number of mechanical operations	12000

Dimensions

Width of installed product	18 mm
----------------------------	-------

Installation, mounting

Tightening torque	1,2Nm
Factory fitted	no

Connection

Connection cross-sect. rigid cable	6mm ²
Connection cross-sect. flexible conductor	4mm ²
Type of connection	with screw
Type of contacts	auxiliary contact 1NC+1NO alarm contact 1NC+1NO

Equipment

Quantity of NC contacts	1
Quantity of NO contacts	1

Standards

European directive WEEE	concerned
-------------------------	-----------

Use conditions

Storage temperature	-40 to 80 °C
Air humidity protection	95% / 80°C