



Motion detector comfort 220° white

EE860

Architecture

Fixing mode	surface-mounting
-------------	------------------

Functions

- Presence simulation
- can be used as a single unit, main device or extension unit
- with 2 operating modes: time- and light-dependent switch on or pulse mode

Main electrical features

Frequency	50/60 Hz
-----------	----------

Voltage

Operating voltage	230 V~ +10%/-15%
-------------------	------------------

Power

Power consumption (standby)	~ 1,2 W
Incandescent bulb power	2300 W

- low intrinsic energy requirement
- energy saving by means of presence and brightness-dependent ON and OFF switching of light

Measurement

Detection field, semi-circular shaped	~ 8 x 16 m
---------------------------------------	------------

Reach distance

Range, side	each ~ 8 m
-------------	------------

Camera

- Lens setting horizontal $\pm 80^\circ$
- Lens setting vertical $-30 \dots +90^\circ$

Cover, door

- with cover elements to limit the detection field

Power supply

Supply voltage 230 V +10% / -15%

Detection

Frontal detecting distance 16 m
Side detecting distance 10 m
Detection angle 220 °
Detection angle 220 °
Diameter of the floor detection area 16 m

Materials

Colour white

Dimensions

Height of installed product 2,5 m
Recommended installation height 2,5 m

Lighting control

Brightness measurement range 5/1000 Lux
Fluorescent lamps with electronical ballast (EB) 580 W
Response brightness, adjustable ~ 5 1000 lx

Fluorescent bulbs control

Energy-saving lamps 20 x 20 W
Fluorescent lamps parallel compensated 400 W /47 µF

LED control

230V LED lamps 20 x 20 W
- with LED detection and mode indicator

Incandescent bulbs control

12 V halogen lamps 1500 W
230 V incandescent lamps and halogen lamps 2300 W

Installation, mounting

- for wall and ceiling mounting, corner installation with adapter

Connection

Connection type quick connect
Type of contacts contact floating
- with screw terminals

Cable

- with cable entry

Settings

Time delayed range 5s to 30 min

Delay time, adjustable 5 s 30 mn

- with potentiometers for setting the response brightness and delay time without dismantling

Scope of delivery

- with fitting material

Equipment

Remote controllable EE806

- with potential-free normally-open contact

- vertically slewing and horizontally rotating

Safety

Protection index IP IP55

Use conditions

Operating temperature -20 55 °C

Storage/transport temperature -20 60 °C

Identification

Application, usage Motion detector

Main design line Motion detectors
