



EPN510

Latching relay 1NO 230V

<b>Main electrical features</b>	
Frequency	50/60 Hz
Rated operational voltage Ue	250 V
<b>Voltage</b>	
Rated insulation voltage	250 V
Command voltage AC	230 V
DC control voltage	110 V
<b>Electric current</b>	
Quiescent current	6 mA
Rating	16 A
<b>Power</b>	
Inrush power absorbed	25 VA
Total power loss under IN	1,2 W
<b>Resistance</b>	
Winding resistance	1225 ?
<b>Endurance</b>	
Electrical durability at nominal load in AC21in operating cycles	150000
Number of mechanical operations	500000
<b>Dimensions</b>	
Depth of installed product	63 mm
Height of installed product	83 mm
Width of installed product	17,5 mm
<b>Installation, mounting</b>	
Tightening torque	1,6Nm

#### Connection

Connection cross-sect. rigid cable	1,5 / 10mm <sup>2</sup>
Connection cross-sect. flexible conductor	1 / 6mm <sup>2</sup>
Type of connection	with screw
Number of contacts	1
Type of contacts	1NO

#### Equipment

Type of latching relay	electromechanic
------------------------	-----------------

#### Use

Pulse duration	50 ms
----------------	-------

#### Standards

European directive WEEE	concerned
-------------------------	-----------

#### Safety

Protection index IP	IP20
---------------------	------

#### Use conditions

Storage temperature	-40 to 80 °C
---------------------	--------------

#### Identification

Device family	EP
---------------	----