



ESC080

**Auxiliary contact 6A, 1NO+1NC**

Technische Merkmale

**Main electrical features**

Rated operational voltage U <sub>e</sub>	230 V
--	-------

**Voltage**

Rated insulation voltage	240 V
Rated impulse withstand voltage	4 kV

**Electric current**

Acceptable current rating with AC1	6 A
Rating	6 A

**Power**

Total power loss under I <sub>N</sub>	0,1 W
---------------------------------------	-------

**Endurance**

Electric endurance in number of cycles	30000
Number of mechanical operations	100000

**Dimensions**

Depth of installed product	60 mm
Height of installed product	83 mm
Width of installed product	11 mm

**Connection**

Max cable connect. cross section (flexible) for control	1 to 6 mm <sup>2</sup>
Connection cross-section of the control cable solid	1 to 10 mm <sup>2</sup>
Connection cross-sect. rigid cable	1 / 6mm <sup>2</sup>
Connection cross-sect. flexible conductor	1 / 6mm <sup>2</sup>
Type of connection	with screw
Number of contacts	2
Type of contacts	1NC+1NO

**Standards**

European directive WEEE	concerned
-------------------------	-----------

**Safety**

Protection class	isol.class II
------------------	---------------

**Use conditions**

Storage temperature	-40 to 80 °C
---------------------	--------------

**Identification**

Device family	ESC
---------------	-----