

-40 to 80 °C



SF118F

2 ways changeover 25A 1P 250V

Technische Merkmale

Storage temperature

	rc	L				
Δ	rc	nı	TΡ	רח	ш	re

Main electrical features Rated operational voltage Ue 250 V Power Total power loss under IN 0,9 W Endurance Number of mechanical operations 150000 Dimensions Depth of installed product 71 mm Height of installed product 83 mm Width of installed product 18 mm Installation, mounting Tightening torque 2,9Nm Connection Connection 2,9Nm Type of connection with screw Number of contacts 1 changeover Standards European directive WEEE not concerned Safety	Architecture	
Rated operational voltage Ue 250 V Power Total power loss under IN 0,9 W Endurance Number of mechanical operations 150000 Dimensions Depth of installed product 71 mm Height of installed product 83 mm Width of installed product 18 mm Installation, mounting Tightening torque 2,9Nm Connection Connection cross-sect. rigid cable 16mmm Connection cross-sect. flexible conductor 10mmm Type of connects Number of contacts 1 changeover Standards European directive WEEE not concerned Safety Protection index IP IP20	Number of poles	1 P
Power Total power loss under IN 0,9 W Endurance Number of mechanical operations 150000 Dimensions Depth of installed product 71 mm Height of installed product 83 mm Width of installed product 18 mm Installation, mounting Tightening torque 2,9Nm Connection Connection cross-sect. rigid cable 16mmi Connection cross-sect. flexible conductor 10mmi Type of connection with screw Number of contacts 1 changeover Standards European directive WEEE not concerned Safety Protection index IP IP20	Main electrical features	
Total power loss under IN 0,9 W Endurance Number of mechanical operations 150000 Dimensions Depth of installed product 71 mm Height of installed product 83 mm Width of installed product 18 mm Installation, mounting Tightening torque 2,9Nm Connection Connection cross-sect. rigid cable 16mm Type of connection with screw Number of contacts 1 changeover 1 changeov	Rated operational voltage Ue	250 V
Endurance Number of mechanical operations 150000 Dimensions Depth of installed product 71 mm Height of installed product 83 mm Width of installed product 18 mm Installation, mounting Tightening torque 2,9Nm Connection Connection cross-sect. rigid cable 16mm Connection cross-sect. flexible conductor 10mm Type of connection with screw Number of contacts 1 changeover Standards European directive WEEE not concerned Safety Protection index IP IP20	Power	
Number of mechanical operations 150000 Dimensions Depth of installed product 71 mm Height of installed product 83 mm Width of installed product 18 mm Installation, mounting Tightening torque 2,9Nm Connection Connection Connection cross-sect. rigid cable 16mm Type of connection cross-sect. flexible conductor 10mm Type of connection with screw Number of contacts 1 changeover Standards European directive WEEE not concerned Safety Protection index IP IP20	Total power loss under IN	0,9 W
Dimensions Depth of installed product 71 mm Height of installed product 83 mm Width of installed product 18 mm Installation, mounting Tightening torque 2,9Nm Connection Connection Connection cross-sect. rigid cable 16mm Connection cross-sect. flexible conductor 10mm Type of connection with screw Number of contacts 1 changeover Standards European directive WEEE not concerned Safety Protection index IP	Endurance	
Depth of installed product 83 mm Height of installed product 18 mm Width of installed product 18 mm Installation, mounting Tightening torque 2,9Nm Connection Connection cross-sect. rigid cable 16 mm Connection cross-sect. flexible conductor 10 mm Type of connection with screw Number of contacts 1 changeover Standards European directive WEEE not concerned Safety Protection index IP IP20	Number of mechanical operations	150000
Height of installed product 83 mm Width of installed product 18 mm Installation, mounting Tightening torque 2,9Nm Connection Connection cross-sect. rigid cable 16mm Connection cross-sect. flexible conductor 10mm Type of connection with screw Number of contacts 1 Type of contacts 1 Type of contacts 1 changeover Standards European directive WEEE not concerned Safety Protection index IP IP20	Dimensions	
Installation, mounting Tightening torque 2,9Nm Connection Connection cross-sect. rigid cable 16mm² Connection cross-sect. flexible conductor 10mm² Type of connection with screw Number of contacts 1 Type of contacts 1 Type of contacts 1 changeover Standards European directive WEEE not concerned Safety Protection index IP IP20	Depth of installed product	71 mm
Installation, mounting Tightening torque 2,9Nm Connection Connection cross-sect. rigid cable 16mm² Connection cross-sect. flexible conductor 10mm² Type of connection with screw Number of contacts 1 Type of contacts 1 Type of contacts 1 changeover Standards European directive WEEE not concerned Safety Protection index IP IP20	Height of installed product	83 mm
Tightening torque 2,9Nm Connection Connection cross-sect. rigid cable 16mm² Connection cross-sect. flexible conductor 10mm² Type of connection with screw Number of contacts 1 Type of contacts 1 Type of contacts 1 Changeover Standards European directive WEEE not concerned Safety Protection index IP IP20	Width of installed product	18 mm
Connection Connection cross-sect. rigid cable 16mm² Connection cross-sect. flexible conductor 10mm² Type of connection with screw Number of contacts 1 Type of contacts 1 Type of contacts 1 changeover Standards European directive WEEE not concerned Safety Protection index IP IP20	Installation, mounting	
Connection cross-sect. rigid cable 16mm² Connection cross-sect. flexible conductor 10mm² Type of connection with screw Number of contacts 1 Type of contacts 1 changeover Standards European directive WEEE not concerned Safety Protection index IP IP20	Tightening torque	2,9Nm
Connection cross-sect. flexible conductor Type of connection with screw Number of contacts Type of contacts Type of contacts 1 changeover Standards European directive WEEE not concerned Safety Protection index IP IP20	Connection	
Type of connection with screw Number of contacts 1 Type of contacts 1 changeover Standards European directive WEEE not concerned Safety Protection index IP IP20	Connection cross-sect. rigid cable	16mm²
Number of contacts Type of contacts 1 changeover Standards European directive WEEE not concerned Safety Protection index IP IP20	Connection cross-sect. flexible conductor	10mm²
Type of contacts 1 changeover Standards European directive WEEE not concerned Safety Protection index IP IP20	Type of connection	with screw
Standards European directive WEEE not concerned Safety Protection index IP IP20	Number of contacts	1
European directive WEEE not concerned Safety Protection index IP IP20	Type of contacts	1 changeover
Safety Protection index IP IP20	Standards	
Protection index IP IP20	European directive WEEE	not concerned
	Safety	
Use conditions	Protection index IP	IP20
	Use conditions	