



EG071

## Weekly time switch 1 channel

### Architecture

Fixing mode	Din-Rail
-------------	----------

### Functions

Number of function channels	1
-----------------------------	---

### Configuration

- change-over contact

### Controls and indicators

- LC display

### Main electrical features

Frequency	50 Hz
Rated operational voltage Ue	230 V

### Voltage

Operating voltage	230 V~
-------------------	--------

### Power

Power consumed	1 VA
Loss power at full load	~ 1 W
Total power loss under IN	1 W
Power dissipation per coil	1 W

### Measurement

Running accuracy	± 1 s/day
------------------	-----------

### Battery

Power reserve [years]	~ 3 a
- with lithium coin cell battery type: CR1632	

### Dimensions

Depth of installed product	64 mm
Height of installed product	92 mm
Width of installed product	18 mm
Width of rail mounted device (RMD)	1 modules

### Incandescent bulbs control

230 V incandescent lamps and halogen lamps	max. 1000 W
Max. power with incandescent lamps	1000 W

### Installation, mounting

Mounting type	din-Rail
- for mounting on DIN rail	

### Connection

Conductor cross-section (flexible)	1 4 mm <sup>2</sup>
Conductor cross-section (rigid)	1 4 mm <sup>2</sup>
Connection cross-sect. rigid cable	1 / 4mm <sup>2</sup>
Connection cross-sect. flexible conductor	1 / 4mm <sup>2</sup>
Type of connection	with screw
Number of contacts	1
Type of contacts	1 changeover
- with screw terminals	
- with potential-free switching contact	

### Settings

Summer / Winter time change	manual
Shortest switching time	1 mn
Program cycles	Programme cycles: 1 x 7 days
Programming cycle	1X7D.
Type of programming	digital

### Equipment

Number of program steps	20
Number of switching times for on/off	20
Number of channels	1
Supply failure reserve	3 years

### Use

Cycle	weekly
-------	--------

### Safety

Protection index IP	IP20
---------------------	------

### Use conditions

Operating temperature	-10 50 °C
Working accuracy	1
Storage temperature	-10 to 60 °C
Storage/transport temperature	-10 60 °C

**Identification**

---

Main design line

Light control

---