

Indicator lights and push buttons

These products are used for remote controlling signalisation of any event in any electric installation (domestic, tertiary &

industrial) LED technology providing longer life, new design, integrated label holder

Connection capacity :

- 10 mm² rigid
- 6 mm² flexible

Standard conformity :

IEC 62094-1 for indicator lights

	Designation	Characteristics	Width in 17.5 mm	Pack qty.	Cat. ref.
	Single indicator light 230 V ~ 	with light : green	1	12	SVN 121
		red	1	12	SVN 122
		orange	1	12	SVN 123
		blue	1	12	SVN 124
		color less	1	12	SVN 125
	Double indicator light 230 V ~ 	with light: green and red	1	12	SVN 126
		color less 2x	1	12	SVN 128
	Triple indicator light 	with light: red	1	12	SVN 127
		red/orange/green	1	12	SVN129
		green	1	12	SVN 221
	Low voltage indicator lights 12 to 48 V AC/DC 	with light green	1	12	SVN 131
		red	1	12	SVN 132
		orange	1	12	SVN 133
		blue	1	12	SVN 134
		color less	1	12	SVN 135

Hour counters

Technical characteristics

- Voltage: 230V +/- 15%, 50 Hz
- Connection: in parallel to the load

	Designation	Characteristics	Width in 17.5mm	Pack qty.	Cat. ref.
	Hours counter	230V 50Hz	2	1	EC 100

EC 100