




























Push buttons:
2 versions :
impulse push buttons
latching push buttons

These versions with indicator lights are equipped with green or red diffuser. (led technology)

Connection capacity :
- 10mm² rigid,
- 6mm² flexible.

Standard conformity :
IEC 60947-5-1 for push buttons
IEC 62094-1 for indicator lights

	<i>Designation</i>	<i>Characteristics</i>	<i>Width in 17.5 mm</i>	<i>Pack qty.</i>	<i>Cat. ref.</i>	
 SVN 311	Impulse push button					
		16 A - 250 V ~ without indicator light contact: 1NO	1	12	SVN 311	
		contact: 1NC	1	12	SVN 321	
		contacts: 2NO	1	12	SVN 331	
		contacts: 2NC	1	12	SVN 341	
		contacts: 1NO+1NC	1	12	SVN 351	
		contacts: 2NO	1	12	SVN 371	
		contacts: 1NO+1NC	1	12	SVN 391	
	 SVN 391	with indicator light :				
			contact: 1NO green	1	12	SVN 411
		contact: 1NC red	1	12	SVN 422	
		contacts: 2NO red	1	12	SVN 432	
		contacts: 2NC green	1	12	SVN 441	
		contacts: 1NO+1NC red	1	12	SVN 452	
 SVN 411		16 A - 12/48 V AC/DC with indicator light				
			contacts: 2NO green	1	12	SVN461
			contacts: 2 NO red	1	12	SVN 462
			with indicator light contacts: 2NO green	1	12	SVN 463
	contacts: 2 NO red	1	12	SVN 464		
 SVN 422	Latching push buttons					
	16 A - 250 V ~ without indicator light					
		contact: 1NO	1	12	SVN 312	
		contact: 1NC	1	12	SVN 322	
		contacts: 2NO	1	12	SVN 332	
		contacts: 2NC	1	12	SVN 342	
		contacts: 1NO+1NC	1	12	SVN 352	
	with indicator light :					
		contact: 1 NO green	1	12	SVN 413	
		contacts: 2 NO green	1	12	SVN 433	