



Description
For use as a switch disconnecter in all types of circuit.

Complies with : BS EN 60 947-3 all ratings

Technical data
utilisation category
AC 22A, 230V/400V

In : 16, 25, 32A
Shrouded cable clamps
connection capacity:
16mm² rigid conductor
10mm² flexible conductor
In : 40, 63A
Cable clamps,
connection capacity:
25mm² rigid conductor
16mm² flexible conductor

In : 80A, 125A
Cable clamps
connection capacity:
50mm² rigid conductor
35mm² flexible conductor
All switches have a green / red indication on the handle giving positive contact indication.

Use MZN175 as locking device

	<i>Designation</i>	<i>Cat Ref.</i> <i>1 Pole</i>	<i>Cat Ref.</i> <i>2 Pole</i>	<i>Cat Ref.</i> <i>3 Pole</i>	<i>Cat Ref.</i> <i>4 Pole</i>
	16A	SBN116	SBN216	SBN316	SBN416
	16A with indicator light	SBB116	SBB216	-	-
	25A	SBN125	SBN225	SBN325	SBN425
	25A with indicator light	SBB125	SBB225	-	-
	32A	SBN132	SBN232	SBN332	SBN432
	32A with indicator light	SBB132	SBB232	-	-
	32A with large terminal	SBN133	SBN233	SBN333	SBN433
	40A	SBN140	SBN240	SBN340	SBN440
	63A	SBN163	SBN263	SBN363	SBN463
	63A with large terminal	SBN164	SBN264	SBN364	SBN464
	80A	SBN180	SBN280	SBN380	SBN480
	100A	SBN190	SBN290	SBN390	SBN490
	125A	SBN199	SBN299	SBN399	SBN499
	Auxilliary contact	ESC080			

Modular changeover switches

	<i>Rating</i>	<i>Toggle</i> <i>Operation</i> <i>(3 position)</i>	<i>Cat Ref.</i> <i>1 Pole</i>	<i>Cat Ref.</i> <i>2 Pole</i>	<i>Cat Ref.</i> <i>3 Pole</i>	<i>Cat Ref.</i> <i>4 Pole</i>
	25A	I - 0 - II	SFT125	SFT225	-	-
	40A	I - 0 - II	SFT140	SFT240	SFT340	SFT440
	63A	I - 0 - II	-	SF263	-	SF463