



**Characteristics**

- Easy to install
- Removable DIN chassis
- Height adjustable DIN chassis
- Centre distance between two rows is 150 mm
- Removable door
- Removable prepunched top and bottom gland plates

**Technical data**

- 1.2mm thickness sheet steel with Epoxy powder coating in RAL 9002
- Suitable for modular incomers and outgoings only

- Accessories like key lock, joining kits, etc.
- Boards can be assembled vertically



DR32S

<i>Designation</i>	<i>No. of rows</i>	<i>No. of Modules</i>	<i>Cat. Ref. Surface mounted</i>	<i>Cat. Ref. Flush mounted</i>
<b>DIN Rail Distribution boards 16 module</b>	1	16	<b>DR16S</b>	<b>DR16F</b>
	2	32	<b>DR32S</b>	<b>DR32F</b>
	3	48	<b>DR48S</b>	<b>DR48F</b>
	4	64	<b>DR64S</b>	<b>DR64F</b>
	5	80	<b>DR80S</b>	<b>DR80F</b>
	6	96	<b>DR96S</b>	<b>DR96F</b>
<b>DIN Rail Distribution boards 24 module</b>	4	96	<b>DR424S</b>	<b>DR424F</b>
	5	120	<b>DR524S</b>	<b>DR524F</b>
	6	144	<b>DR624S</b>	<b>DR624F</b>

<i>Designation</i>	<i>Cat. Ref</i>
<b>Accessories</b>	
Joining kits for surface boards (16mod DB)	<b>JK01SK</b>
Joining kits for flush boards (16mod DB)	<b>JK01FK</b>
1 mod blanking strip	<b>P032H</b>
Key lock	<b>VZ794N</b>