

Load break switches 20 to 125A



HAB406

Designation	Characteristics	In/A	Width in 17.5mm		Cat. ref.	
			3P	4P	3P	4P
Load break switches visible breaking	disconnector	20A	2.5	3.5	HAB302	HAB402
	modular design	32A	2.5	3.5	HAB303	HAB403
	IP20	40A	2.5	3.5	HAB304	HAB404
	AC23	63A	2.5	3.5	HAB306	HAB406
		63A	3	4	HAC306	HAC406
		80A	3	4	HAC308	HAC408
		100A	3	4	HAC310	HAC410
		100A	4.5	6	HAD310	HAD410
		125A	4.5	6	HAD312	HAD412

Auxiliaries contacts In = 10A	1O + 1F	0.5	0.5	HZC311	HZC311
	2F	0.5	0.5	HZC312	HZC312

External handle IP55 locked with 3 padlocks	for LBS 20 to 100A	HZC010	HZC010
	for LBS 100 to 125A	HZC011	HZC011
	for LBS 100 to 125A	HZC014	HZC014

Shaft extension	20 to 100A, 150mm	HZC111	HZC111
	20 to 100A, 200mm	HZC112	HZC112
	20 to 100A, 320mm	HZC113	HZC113
	100 to 125A, 150mm	HZC114	HZC114
	100 to 125A, 200mm	HZC115	HZC115
	100 to 125A, 320mm	HZC116	HZC116

Terminal shrouds top and bottom 2 pieces / packaging	20 to 63A	HZC211	HZC212
	63 to 100A	HZC213	HZC214
	100 to 125A	HZC215	HZC216



HZC014

Load break switches

160A, 200A, 250A for use as distribution board incomer

Designation	In/A	Cat. ref. 3P
-------------	------	-----------------



JK160S


Load break switches AC22/AC23	160A	JK160S
	200A	JK200S
	250A	JK250S



JK200S



HA358



HZC101

<i>Designation</i>	<i>Characteristics</i>	<i>In/A</i>	<i>Cat. ref.</i>	
			<i>3P</i>	<i>4P</i>
Load break switches with handle	direct rotary handle AC22 and AC23	125A	HA351	HA451
		160A	HA352	HA452
		200A	HA353M	HA453M
		250A	HA354	HA454
		315A	HA355M	HA455M
		400A	HA357	HA457
		630A	HA358	HA458
		800A	HA360	HA460
		1250A	HA362	HA462
		1600A	HA364	HA464
		Auxiliaries contacts		
Rotary handle	for extended shaft			
	- 125 to 630A		HZC002	HZC002
	- 800 to 1600A		HZC003	HZC003
	- double hand		HZA001	HZA001
Shaft extension	125 to 630A, 200mm		HZC101	HZC101
	125 to 630A, 320mm		HZC102	HZC102
	800 to 1600A, 200mm		HZC105	HZC105
	800 to 1600A, 320mm		HZC106	HZC106