

- Complies with BS EN 60669-1 a.c. only SS227 MS616
- 'X' rated - No need to derate for fluorescent loads
- Supplied with M3.5 x 14mm long fixing screws.
- 1, 2, 3 and 4 gang units supplied with two knockouts matching the surface box.
- Capacity of each terminal: 2 x 2.5mm² conductors 5 x 1.5mm² earth terminal (box).
- Other switches are available without mounting boxes on request.
- Knockouts accept 20mm diameter conduit
- Earth terminal supplied with each box.



XP120MC



XP420MC

Designation	Characteristics	Cat. ref.
Single pole plate switches	1 gang 2 way	XP120MC
	2 gang 2 way	XP220MC
	3 gang 2 way	XP320MC
	4 gang 2 way (size 2)	XP420MC

20A double pole control switches

- Complies with BS EN 60669-1 a.c. only SS227 MS616
- Supplied with M3.5 x 14mm long fixing screws.
- Capacity of each terminal: 3 x 2.5mm² conductors



XR206MC

Designation	Characteristics	Cat. ref.
Double pole control switch	20A with neon	XR206MC

45A double pole control switches

- Complies with BS EN 60669-1 a.c. only SS227 MS616
- Supplied with M3.5 x 14mm long fixing screws.
- Capacity of each terminal: 1 x 16mm² conductors 1 x 10mm² conductors



XR457MC

Designation	Characteristics	Cat. ref.
Double pole control switch	45A with neon	XR457MC

- Complies with BS 1363 Pt 2, a.c. only
SS145
MS589
- All switched units are double pole.
- Supplied with M3.5 x 14mm long fixing screws
- All terminal screws upward facing for ease of installation.
- Capacity of each terminal: 4 x 2.5mm².
- Tough plastic back for durability.



XS114MC



XS215MC

Designation	Characteristics	Cat. ref.
Socket outlets	13A single switched	XS114MC
	13A double switched (size 2)	XS214MC
	13A single switched with neon	XS115MC
	13A double switched with neon (size 2)	XS215MC

15A sockets

- Complies with BS 546
SS472
MS589
- Supplied with M3.5 x 14mm long fixing screws
- Capacity of each terminal:
3 x 2.5mm² conductors
3 x 2.5mm² earth conductors.



XS916MC

Designation	Characteristics	Cat. ref.
Socket outlets	15A round pin switched	XS916MC

Fused connection units

- Complies with BS 1363 Pt 4, a.c. only
SS403
MS589
- All switched units are double pole.
- Supplied with M3.5 x 14mm long fixing screws.
- Cable clamp accommodates up to 2,5mm² flexible cord.
- Optional flex outlet - for choice of use
- Capacity of each terminal: 4 x 2,5mm²
- All units fitted with a 13A fuse link to BS 1362, can be supplied with 2A, 5A fuse link.



XR134MC



XR137MC

Designation	Characteristics	Cat. ref.
Fused connection units	13A double pole switch fused with neon	XR134MC
	13A double pole switch fused with neon and flex outlet	XR137MC