

Technical characteristics

Base pre-drilled with lid.

Standard length: 2 Mtr.

Material: Rigid PVC


Colour: Grey (RAL 7030)

Fire classification : UL 94VO.


Base and lid




	Dimensions (Height x Width) in mm	Qty. per pack in Mtrs.	Cat. ref.
 Height 25 mm	25 x 25	50m	BA7A25025
	25 x 40	48m	BA7A25040
 Height 40 mm	40 x 25	48m	BA7A40025
	40 x 40	50m	BA7A40040
	40 x 60	40m	BA7A40060
	40 x 80	30m	BA7A40080
	40 x 100	20m	BA7A40100
 Height 60 mm	60 x 25	60m	BA7A60025
	60 x 40	40m	BA7A60040
	60 x 60	24m	BA7A60060
	60 x 80	20m	BA7A60080
	60 x 100	16m	BA7A60100
	60 x 120	12m	BA7A60120
 Height 80 mm	80 x 25	20m	BA7A80025
	80 x 40	20m	BA7A80040
	80 x 60	20m	BA7A80060
	80 x 80	16m	BA7A80080
	80 x 100	12m	BA7A80100
	80 x 120	16m	BA7A80120
 Height 100 mm	100 x 60	16m	BA7A100060
	100 x 80	16m	BA7A100080
	100 x 100	12m	BA7A100100




Dimensions
height 25 mm
ducting 25 x 40




Dimensions
height 100 mm



Perforation details
DIN 43659
EN 50 085-2-3
width 80, 100 and 120 mm



Dimensions
height 60 and 80 mm



Perforation details
DIN 43659
EN 50 085-2-3
width 25, 40 and 60 mm