

## Contactor 64A-AC3 / coil 110V AC 50/60Hz

### Architecture

Type of pole	3 P
--------------	-----

### Compatibility

Compatible with DIN rail mounting	yes
-----------------------------------	-----

### Main electrical features

Type of supply voltage	AC
Rated operational voltage Ue	660 V

### Voltage

Rated insulation voltage	660 V
Command voltage AC	110 V

### Electric current

Acceptable current rating with AC1	80 A
Rated operational current in AC3	64 A
Thermal rated current outside of housings	80 A

### Power

Contact rating with 400 V in AC3	30 kW
----------------------------------	-------

### Endurance

Electric endurance in number of cycles	500000
Number of mechanical operations	5000000

### Measurement

Relative humidity (without condensation)	45 85 %
--	---------

### Dimensions

Depth of installed product	123 mm
Height of installed product	116 mm
Width of installed product	94 mm

### Connection

Type of connection	with screw
Connection cross section of access and exit with screws, for flexible conductor	10/35 mm <sup>2</sup>
Connection cross-section of input and output with screws, for massive conductors	10/35 mm <sup>2</sup>

### Equipment

Number of auxiliary contacts as normally closed contact	2
Number of auxiliary contacts as normally open contact	2
Quantity of NO contacts	3

**Use cases**

---

Category of use	AC3
-----------------	-----

---

**Standards**

---

Standard text	IEC 60 947-4-1
European directive WEEE	not concerned

---

**Use conditions**

---

Altitude	2000 m
Storage temperature	-40 to 80 °C

---

**Identification**

---

Device family	EW
---------------	----

---