

Contactors 64A-AC3 / coil 415V 50 Hz

Technische Merkmale

Architecture

Type of pole	3 P
--------------	-----

Compatibility

Compatible with DIN rail mounting	yes
-----------------------------------	-----

Main electrical features

Type of supply voltage	AC
------------------------	----

Rated operational voltage Ue	660 V
------------------------------	-------

Voltage

Rated insulation voltage	660 V
--------------------------	-------

Command voltage AC	415 V
--------------------	-------

Electric current

Acceptable current rating with AC1	80 A
------------------------------------	------

Rated operational current in AC3	64 A
----------------------------------	------

Thermal rated current outside of housings	80 A
---	------

Power

Contact rating with 400 V in AC3	30 kW
----------------------------------	-------

Endurance

Electric endurance in number of cycles	500000
--	--------

Number of mechanical operations	5000000
---------------------------------	---------

Measurement

Relative humidity (without condensation)	45 ... 85 %
--	-------------

Dimensions

Depth of installed product	123 mm
----------------------------	--------

Height of installed product	116 mm
-----------------------------	--------

Width of installed product	94 mm
----------------------------	-------

Connection

Type of connection	with screw
--------------------	------------

Connection cross section of access and exit with screws, for flexible conductor	10/35 mm ²
---	-----------------------

Connection cross-section of input and output with screws, for massive conductors	10/35 mm ²
--	-----------------------

Equipment

Number of auxiliary contacts as normally closed contact	2
Number of auxiliary contacts as normally open contact	2
Quantity of NO contacts	3

Use cases

Category of use	AC3
-----------------	-----

Standards

Standard text	IEC 60 947-4-1
European directive WEEE	not concerned

Use conditions

Altitude	2000 m
Storage temperature	-40 to 80 °C

Identification

Device family	EW
---------------	----