



CHILD SOCK.HI.CO.ARS.BRON

47570001

Architecture

Design according to DIN 49440

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

Cover, door

- when opening hinged cover, it can be arrested in end position
- Central cover plate

Materials

RAL colour	RAL 3012 - Beige red
Colour of design line	light bronze
Colour	hellbronze optics
Colour	bronze
Material / workmanship	aluminium lacquered
Material	Aluminium
Surface appearance	matt

Dimensions

Insertion depth 32 mm

Installation, mounting

- mounting orientation of insert selectable in 45° steps
- with spreader claws

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1
- with plug-in terminals	

Use

- enhanced contact protection
 - Mounting orientation variable in 45° steps
-

Safety

Protection index IP	IP20
IK protection code against mechanical impacts	07
Enhanced contact protection (child protection)	according to IEC 60884-1
Enhanced contact protection (child protection)	according to VDE 0620-1

- Enhanced contact protection

Identification

Main design line	Berker Arsys
------------------	--------------

Instructions

-
- Specially suited for combining several socket outlets if right angle plugs are used.
-