



CHILD SOCK.HI.CO.ARSYS GO

47570002

Architecture

Design	according to DIN 49440
--------	------------------------

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

Cover, door

- when opening hinged cover, it can be arrested in end position
- Central cover plate

Materials

RAL colour	RAL 1004 - Golden yellow
Design lines special colours	gold
Colour	gold optics
Colour	gold
Material / workmanship	aluminium, anodised
Material	Aluminium
Surface appearance	matt

Dimensions

Insertion depth	32 mm
-----------------	-------

Installation, mounting

- mounting orientation of insert selectable in 45° steps
- with spreader claws

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1

- with plug-in terminals

Use

- enhanced contact protection
 - Mounting orientation variable in 45° steps
-

Safety

Protection index IP	IP20
IK protection code against mechanical impacts	02
Enhanced contact protection (child protection)	according to IEC 60884-1
Enhanced contact protection (child protection)	according to VDE 0620-1
- Enhanced contact protection	

Identification

Main design line	Berker Arsys
------------------	--------------

Instructions

- Specially suited for combining several socket outlets if right angle plugs are used.
-