



Ind sta VID comfort 2w black gl TOUCH

REA665X

Functions	
Security functions	special functions and extended menu lockable using DIP-switches, privacy function, video privacy function, manual camera activation lockable
Special functions	manual camera and door activation/change-over, automatic door release (automatic door release), floor door release automatic, direct door release, internal connection, 8 internal call destinations can be configured, - Parallel call to call push-button intercom device address 0
System functions	acoustic and optical call signalling via LED and display, Storey call forwarding, parallel operation of up to 3 indoor stations, automatic display switch off after 3 minutes, call waiting during current call, Concierge call, Image memory function in connection with IP gateway 2-wire
Configuration	
Configuration	8 of 13 special functions can be configured as menu entries, device configuration via menu and 4pole DIP-switch, service page lockable using DIP-switches
Controls and indicators	
<ul style="list-style-type: none">- illuminated TFT colour display- display of the calling door/internal station number- display of moving camera pictures from video door stations or external cameras- icon bar for displaying menu button assignment	

Voltage

Operating voltage over bus	24 V DC
----------------------------	---------

Electric current

Current consumption (idle)	<= 12 mA
Current consumption (operation)	<= 220 mA

Power

Power consumption (operation)	5 W
Power consumption (standby)	~ 0,18 W

Resistance

Terminator (terminating resistor), can be clamped	100 ?
---	-------

Measurement

Relative humidity (without condensation)	0 65 %
--	--------

Screen

Display diagonal	88,9 mm
Resolution graphical display	320 x 240 px
Display diagonal	8,9 cm (3,5")

Materials

RAL colour	RAL 9005 - Jet black
Colour of design line	black
Colour	black
Material	plastic
Surface appearance	glossy
- plastic, thermoplastic	

Dimensions

Dimensions without frame (W x H x D)	93 x 144,5 x 16 mm
Dimensions of display (W x H)	72,5 x 53,5 mm

Installation, mounting

For surface-mounting on a flat surface or on a wall box	according to DIN 49073
- flat surface-mounted installation or onto wall box	
- for vertical mounting	

Connection

Conductor cross-section (connection terminal block)	max. 0,75 mm ²
- connection terminal block with screw terminals	
- for floor call push-button	
- for optional additional power supply	
- 2-wire	

Cable

Conductor Ø	0,5 0,8 mm
-------------	------------

Settings

Audio settings	ring tone volume and microphone sensitivity can be adjusted incrementally
Calling settings	hands-free or Push-to-Talk
Device addressing	rotary coding switch (one-man commissioning)
Display languages	German, English, French, Italian, Dutch
- Display brightness and contrast can be adjusted in stages	

Equipment

Call volume (hands-free)	max. 65 dBA
Menu control	3 menu operation buttons for settings and for triggering the functions appearing in the display, menu access and change-over by horizontal swipe movement on the touch user interface
Ring tone volume (signal)	according to DIN EN 50486
Ring tone volume	max. 78 dB at a distance of 0.5 m

Use

Ring tone melody	16 ring tone melodies, door call, storey call or internal call assignment, shut-off button for ring tone, with status LED
System technology	2-wire

Use conditions

Operating temperature	5 50 °C
Storage/transport temperature	-20 60 °C (storage at > 45°C reduces the service life)

Identification

Main design line	Touch
------------------	-------